



PANTOGRAPHS

by Movie Tech

... premium lighting suspension!

MTS - Manually Operated Pantographs SZM 25-60











PANTOGRAPHS

by Movie Tech

... premium lighting suspension!

MTS - Manually Operated Pantographs SZM 25-60



SZM 25-60

- Transmission: dynamically self-locking drive, 1:20
- Supporting cables: 2 x d = 2mm
- Power outlet: 16 A Schuko socket (alternatively CEE 17)
- DMX XLR 5 socket (optional)
- Upper attachment: DIN TV spigot, d = 28 mm
- Load attachment: DIN TV socket, d = 29 mm
- Operated via operating pole SBV or motorized pole MSB 400
- Safety standards: DGUV Vorschrift 17 (former BGV C1/ VBG 70) and DIN 56950-2 (former DIN 15560)

Manual operating pole SBV or motorized pole MSB



Version	# Item number	Max. payload	 Closed height	Max. drop	Kg Dead weight
SZM 25	312.250 (16A CEE) 313.250 (Schuko)	30 kg	550 mm	2,6 m	10,5 kg
SZM 45	312.450 (16A CEE) 313.450 (Schuko)	30 kg	700 mm	4,6 m	13,5 kg
SZM 50	312.500 (16A CEE) 313.500 (Schuko)	30 kg	750 mm	5,3 m	14,5 kg
SZM 60	312.600 (16A CEE) 313.600 (Schuko)	30 kg	850 mm	6,0 m	16,5 kg



MTS - Media Technical System

We – MTS Media Technical System – have now more than 20 years of experience in designing and manufacturing premium quality lighting suspension for stage and studio. Since 2006 we are part of the MovieTech AG.

Our goal is to manufacture every single product with the **highest possible quality** and to **over-fulfill our customer's expectations.** We are proud to call many of the major broadcasting companies all around the globe our customer-base.

We produce all our products order-related in our **optimized production facility** and thus meet the specific requirements of every individual project. In combination with their reliability our products **simplify the daily work** on stage and in the studio.